

23249

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
1 April 2004 (01.04.2004)

PCT

(10) International Publication Number
WO 2004/027211 A1

- (51) International Patent Classification⁷: E21B 43/12, H02K 16/00
- (21) International Application Number: PCT/GB2003/004009
- (22) International Filing Date: 18 September 2003 (18.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0221630.7 18 September 2002 (18.09.2002) GB
0315848.2 7 July 2003 (07.07.2003) GB
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant and
(72) Inventor: HEAD, Phillip [GB/GB]; Gibb House, Kennel Ride, Ascot, Berks SL5 7NT (GB).
- (74) Agent: HARMAN, Michael; Hillgate Patent Services, 6 Aztec Row, Berners Road, Islington, London N1 0PW (GB).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ELECTRIC MOTORS FOR POWERING DOWNHOLE TOOLS



(57) Abstract: An electric motor for powering downhole tools comprises a first stator (33) including a first set of coil windings (73), a second stator including a second set of windings, an axially located rotatable shaft (92) including a first magnetic element and a second magnetic element, a sealed annular chamber defined by a first tube (96), and an second tube concentrically inside the first tube. The first and second stators are located in the annular chamber, and the first magnetic element being aligned with the first stator such that the first stator when energised can act upon the first magnetic element, and the second magnetic element being aligned with the second stator such that the second stator when energised can act upon the second magnetic element.

WO 2004/027211 A1